

PRODUCT INFORMATION

Purgex™ 3056 Plus Commercial Purging Compound is a ready-to-use blend consisting of active ingredients with a polyethylene carrier. Purgex™ products have mechanical activity for efficient cleaning, foaming action for enhanced mixing and a lubricant for easy removal. Purgex™ thoroughly and safely cleans injection molding machines and hot runner systems.

Physical Description:

- Blend, polyethylene, and an active component
- Non-toxic, non-abrasive, and safe
- Ready to use and easy to remove

Process:	<input checked="" type="checkbox"/> Injection Molding	<input checked="" type="checkbox"/> Injection Blow Molding	<input checked="" type="checkbox"/> Extrusion-Blow Molding	<input checked="" type="checkbox"/> Extrusion-Profile
	<input checked="" type="checkbox"/> Extrusion-Compounding	<input checked="" type="checkbox"/> Extrusion-Sheet	<input type="checkbox"/> Blown Film	
Works Best on These Resins:	<input checked="" type="checkbox"/> Nylon	<input checked="" type="checkbox"/> PBT	<input checked="" type="checkbox"/> POM	
Also Useful for:	<input checked="" type="checkbox"/> PVC-Flexible	<input checked="" type="checkbox"/> PVC-Rigid	<input checked="" type="checkbox"/> Startup	<input checked="" type="checkbox"/> Shutdown
	<input checked="" type="checkbox"/> PET	<input checked="" type="checkbox"/> PPO	<input checked="" type="checkbox"/> PPA	
	<input checked="" type="checkbox"/> Many other resins processed in this temperature range.			
Amount Needed:	1 to 1.5 times barrel capacity, depending upon condition of machine/tool and colorant/additive loading.			
Temperature Range:	380°F to 600°F (193°C to 316°C)			
Recommended for:	<input checked="" type="checkbox"/> Hot Runners	<input checked="" type="checkbox"/> Mixing Nozzles	<input checked="" type="checkbox"/> Check Valves	<input checked="" type="checkbox"/> Accumulators
	<input checked="" type="checkbox"/> Cold Runners	<input checked="" type="checkbox"/> Extrusion Dies	<input checked="" type="checkbox"/> Melt Pumps	

Features & Benefits:

- ✓ Designed for color and/or material changes on engineering resins plus efficient cleaning of hot runner systems, Purgex™ 3056 Plus has proven versatility on a wide range of resins.
- ✓ Engineered for rapid turnaround on color and material changes. Efficiently removes residual contamination.
- ✓ Effectively cleans the barrel, screw, check ring, as well as hot runner systems and is safely processed through hot runner gates as small as .030-inch (0.75mm).
- ✓ Thorough cleaning of melt pumps and is safely processed through dies as small as .030-inch (0.75mm).
- ✓ Active components in Purgex™ 3056 Plus neutralize acid gases generated by PVC.