PURGEX™ 3057 PLUS

Purging Compounds

PRODUCT INFORMATION

Purgex™ 3057 Plus Commercial Purging Compound is a ready-to-use blend consisting of active ingredients with a polyethylene carrier. Purgex products have mechanical activity for efficient cleaning, foaming action for enhanced mixing and a lubricant for easy removal. Purgex thoroughly and safely cleans injection molding machines and hot runner systems.

Physical Description:

- Blend, polyethylene, viscosity modifier, and an active component
- Non-toxic, non-abrasive, and safe
- Ready to use and easy to remove

Processes	Injection Molding; Injection Blow Molding; Extrusion compounding; Extrusion blow molding; Profile extrusion; Sheet extrusion
Listed resins	PA (nylon), PC, PC/ABS, Flexible PVC*, PBT, PET, PMMA, POM, PPA, PPO, Rigid PVC, SAN, ABS, PE, PP-Copolymer, PS, TPEs, TPOs, EVOH, HDPE, LDPE, LLDPE, PP-Homopolymer, PU
Amount needed	1 to 1.5 times barrel capacity, depending on condition of machine/tool and colorant/additive loading.
Temperature range	380-600°F (193-316°C)
Equipment cleaned	Cold Runners, Hot Runners, Check Valves, Mixing Nozzles, Accumulators, Melt Pumps, Extrusion Dies

*Flexible PVC: over 370°F and within the stated grade range. Coverage: Product Selection Guide Matrix, Rev. H, version supplied Nov. 11, 2026. Table aligned Nov. 11, 2026; original sheet revision retained below.

Features & Benefits:

- ✓ Created for more challenging color and/or material changes in engineering resins plus efficient cleaning of hot runner systems, Purgex 3057 Plus has the proven ability to clean low- to mid-range mineral- and glass-filled resins.
- ✓ Designed for rapid turnaround on color and material changes. Efficiently removes residual contamination.
- ✓ Purgex 3057 Plus effectively cleans a wide range of resins from commodity to engineering grades.
- ✓ Effectively cleans the barrel, screw, check ring, as well as hot runner systems and is safely processed through hot runner gates as small as .030-inch (0.75mm).
- ✓ Thorough cleaning of melt pumps and is safely processed through dies as small as .030-inch (0.75mm).

Copyright 2024 Neutrex, Inc. All rights reserved – Revision F: 3/1/24

Houston, TX 77065 USA – Phone 281-807-9449 – Fax 281-807-9748 – sales@purgexonline.com – www.purgexonline.com